

Listing of Claims:

This listing of claims will replace all prior versions, and listings, of claims in this application.

Claims 1-18 (Canceled).

Claim 19 (Currently Amended): A packet processor for processing packets of data received via a network to reproduce the data, comprising:

a receiving buffer for storing received packets;

a reproducing means for reproducing data of the packets based on a reproduction clock;

and

a control means for performing control so as to reproduce data without breaks,

wherein the control means controls the packets ~~having been~~ stored in the receiving buffer by their number without using temporal information received with the packets, holds a reference value for the number of received packets, which is determined beforehand, and causes the reproducing means to start data reproduction when the number of packets exceeds the reference ~~value number~~; monitors a state of the receiving buffer and collects, when the packets ~~[[data]]~~ in the buffer are ~~[[is]]~~ used up, packets ~~[[data]]~~ up to a level corresponding to the reference value before causing the reproducing means to restart data reproduction; and monitors the number of packets in the receiving buffer at intervals of a predetermined time period, and when a result shows increase or decrease in the number of packets with time, the control means, based on the result, modifies a receiving buffer size and the reference value for the number of received packets at which reproduction of data is started.

Claim 20 (Currently Amended): A packet processor for processing packets of data received via a network to reproduce the data, comprising:

a receiving buffer for storing received packets;

a reproducing means for reproducing data of the packets based on a reproduction clock;
and

a control means for performing control so as to reproduce data without breaks,
wherein the control means controls the packets ~~having been~~ stored in the receiving buffer by their number without using temporal information received with the packets, holds a reference value for the number of received packets, which is determined beforehand, and causes the reproducing means to start data reproduction when the number of packets exceeds the reference ~~value number~~; monitors a state of the receiving buffer and discards, when the packets ~~[[data]]~~ in the buffer ~~exceed~~ ~~exceeds~~ a predetermined buffer size, a fixed ~~number amount~~ of packets ~~[[data]]~~ from the buffer; and monitors the number of packets in the receiving buffer at intervals of a predetermined time period, and when a result shows increase or decrease in the number of packets with time, the control means, based on the result, modifies the receiving buffer size and the reference value for the number of received packets at which reproduction of data is started.

Claim 21 (Currently Amended): A packet processor for processing packets of data received via a network to reproduce the data, comprising:

a receiving buffer for storing received packets;
a reproducing means for reproducing data of the packets based on a reproduction clock;
and

a control means for performing control so as to reproduce data without breaks,
wherein the control means controls the packets ~~having been~~ stored in the receiving buffer by their number without using temporal information received with the packets, holds a reference value for the number of received packets, which is determined beforehand, and causes the reproducing means to start data reproduction when the number of packets exceeds the reference ~~value number~~; monitors a state of the receiving buffer and modifies, when the packets ~~[[data]]~~ in the buffer are ~~[[is]]~~ used up, the reference value for the number of received packets at which reproduction of data is started, upon a next reproduction of data; and monitors the number of packets in the receiving buffer at intervals of a predetermined time period, and when a result shows increase or decrease in the number of packets with time, the control means, based on the result, modifies a receiving buffer size and the reference value for the number of received packets at which reproduction of data is started.

Claim 22 (Currently Amended): A packet processor for processing packets of data received via a network to reproduce the data, comprising:
a receiving buffer for storing received packets;
a reproducing means for reproducing data of the packets based on a reproduction clock;
and
a control means for performing control so as to reproduce data without breaks,
wherein the control means controls the packets ~~having been~~ stored in the receiving buffer by their number without using temporal information received with the packets, holds a reference value for the number of received packets, which is determined beforehand, and causes the reproducing means to start data reproduction when the number of packets exceeds the reference ~~value number~~; monitors a state of the receiving buffer and modifies, when the packets ~~[[data]]~~ in the buffer exceed ~~exceeds~~ a predetermined buffer size, the size of the receiving buffer; and monitors the number of packets in the receiving buffer at intervals of a predetermined time period, and when a result shows increase or decrease in the number of packets with time, the control means, based on the result, modifies the receiving buffer size and the reference value for the number of received packets at which reproduction of data is started.

Claim 23 (Currently Amended): A packet processor for processing packets of data received via a network to reproduce the data, comprising:
a receiving buffer for storing received packets;
a reproducing means for reproducing data of the packets based on a reproduction clock;
and
a control means for performing control so as to reproduce data without breaks,
wherein the control means controls the packets ~~having been~~ stored in the receiving buffer by their number without using temporal information received with the packets, holds a reference value for the number of received packets, which is determined beforehand, and causes the reproducing means to start data reproduction when the number of packets exceeds the reference ~~value number~~; monitors a state of the receiving buffer and collects, when the packets ~~[[data]]~~ in the buffer are ~~[[is]]~~ used up, packets ~~[[data]]~~ up to a level corresponding to the reference value before causing the reproducing means to restart data reproduction; and monitors the number of

packets in the receiving buffer at intervals of a predetermined time period, and when a result shows increase or decrease in the number of packets with time, the control means, based on the result, and not based on the temporal information received with the packets, modifies a clock for data reproduction.

Claim 24 (Currently Amended): A packet processor for processing packets of data received via a network to reproduce the data, comprising:
a receiving buffer for storing received packets;
a reproducing means for reproducing data of the packets based on a reproduction clock;
and
a control means for performing control so as to reproduce data without breaks,
wherein the control means controls the packets ~~having been~~ stored in the receiving buffer by their number without using temporal information received with the packets, holds a reference value for the number of received packets, which is determined beforehand, and causes the reproducing means to start data reproduction when the number of packets exceeds the reference ~~value number~~; monitors a state of the receiving buffer and discards, when the packets ~~[[data]]~~ in the buffer ~~exceed~~ ~~exceeds~~ a predetermined buffer size, a fixed number amount of packets ~~[[data]]~~ from the buffer; and monitors the number of packets in the receiving buffer at intervals of a predetermined time period, and when a result shows increase or decrease in the number of packets with time, the control means, based on the result, and not based on the temporal information received with the packets, modifies a clock for data reproduction.

Claim 25 (Currently Amended): A packet processor for processing packets of data received via a network to reproduce the data, comprising:
a receiving buffer for storing received packets;
a reproducing means for reproducing data of the packets based on a reproduction clock;
and
a control means for performing control so as to reproduce data without breaks,
wherein the control means controls the packets ~~having been~~ stored in the receiving buffer by their number without using temporal information received with the packets, holds a reference value for the number of received packets, which is determined beforehand, and causes the

reproducing means to start data reproduction when the number of packets exceeds the reference value number; monitors a state of the receiving buffer and modifies, when the packets ~~[[data]]~~ in the buffer are ~~[[is]]~~ used up, the reference value for the number of received packets at which reproduction of data is started, upon a next reproduction of data; and monitors the number of packets in the receiving buffer at intervals of a predetermined time period, and when a result shows increase or decrease in the number of packets with time, the control means, based on the result, modifies a clock for data reproduction.

Claim 26 (Currently Amended): A packet processor for processing packets of data received via a network to reproduce the data, comprising:
a receiving buffer for storing received packets;
a reproducing means for reproducing data of the packets based on a reproduction clock;
and
a control means for performing control so as to reproduce data without breaks,
wherein the control means controls the packets ~~having been~~ stored in the receiving buffer by their number without using temporal information received with the packets, holds a reference value for the number of received packets, which is determined beforehand, and causes the reproducing means to start data reproduction when the number of packets exceeds the reference value number; monitors a state of the receiving buffer and modifies, when the packets ~~[[data]]~~ in the buffer exceed ~~exceeds~~ a predetermined buffer size, the size of the receiving buffer; and monitors the number of packets in the receiving buffer at intervals of a predetermined time period, and when a result shows increase or decrease in the number of packets with time, the control means, based on the result, and not based on the temporal information received with the packets, modifies a clock for data reproduction.

Claim 27 (Currently Amended): A packet processor for processing packets of data received via a network to reproduce the data, comprising:
a receiving buffer for storing received packets;
a reproducing means for reproducing data of the packets based on a reproduction clock;
and
a control means for performing control so as to reproduce data without breaks,

wherein the control means controls the packets ~~having been~~ stored in the receiving buffer by their number without using temporal information received with the packets, holds a reference value for the number of received packets, which is determined beforehand, and causes the reproducing means to start data reproduction when the number of packets exceeds the reference value number; monitors a state of the receiving buffer and modifies, when the packets ~~[[data]]~~ in the buffer are ~~[[is]]~~ used up, the reference value for the number of received packets at which reproduction of data is started, upon a next reproduction of data; and records ~~[[the]]~~ modifications of the reference value for the number of received packets or a receiving buffer size, continuously from a start of a communication, and if recorded modifications of one type successively occur, the control means, based on the recorded modifications ~~result~~, modifies the receiving buffer size and the reference value for the number of received packets at which reproduction of data is started.

Claim 28 (Currently Amended): A packet processor for processing packets of data received via a network to reproduce the data, comprising:

a receiving buffer for storing received packets;

a reproducing means for reproducing data of the packets based on a reproduction clock;

and

a control means for performing control so as to reproduce data without breaks,

wherein the control means controls the packets ~~having been~~ stored in the receiving buffer by their number without using temporal information received with the packets, holds a reference value for the number of received packets, which is determined beforehand, and causes the reproducing means to start data reproduction when the number of packets exceeds the reference number; monitors a state of the receiving buffer and modifies, when the packets ~~[[data]]~~ in the buffer exceed exceeds a predetermined buffer size, the size of the receiving buffer; and records ~~[[the]]~~ modifications of the reference value for the number of received packets or a receiving buffer size, continuously from a start of a communication, and if recorded modifications of one type successively occur, the control means, based on the recorded modifications ~~result~~, modifies the receiving buffer size and the reference value for the number of received packets at which reproduction of data is started.

Claim 29 (Currently Amended): A packet processor for processing packets of data received via a network to reproduce the data, comprising:

a receiving buffer for storing received packets;

a reproducing means for reproducing data of the packets based on a reproduction clock;

and

a control means for performing control so as to reproduce data without breaks,

wherein the control means controls the packets ~~having been~~ stored in the receiving buffer by their number without using temporal information received with the packets, holds a reference value for the number of received packets, which is determined beforehand, and causes the reproducing means to start data reproduction when the number of packets exceeds the reference ~~value number~~; monitors a state of the receiving buffer and modifies, when the packets ~~[[data]]~~ in the buffer are ~~[[is]]~~ used up, the reference value for the number of received packets at which reproduction of data is started, upon a next reproduction of data; and records ~~[[the]]~~ modifications of the reference value for the number of received packets or a receiving buffer size, continuously from a start of a communication, and if recorded modifications of one type successively occur, the control means, based on the recorded modifications ~~result~~, modifies a clock for data reproduction.

Claim 30 (Currently Amended): A packet processor for processing packets of data received via a network to reproduce the data, comprising:

a receiving buffer for storing received packets;

a reproducing means for reproducing data of the packets based on a reproduction clock;

and

a control means for performing control so as to reproduce data without breaks,

wherein the control means controls the packets ~~having been~~ stored in the receiving buffer by their number without using temporal information received with the packets, holds a reference value for the number of received packets, which is determined beforehand, and causes the reproducing means to start data reproduction when the number of packets exceeds the reference ~~value number~~; monitors a state of the receiving buffer and modifies, when the packets ~~[[data]]~~ in the buffer exceed ~~exceeds~~ a predetermined buffer size, the size of the receiving buffer; and records ~~[[the]]~~ modifications of the reference value for the number of received packets or the

receiving buffer size, continuously from a start of a communication, and if recorded modifications of one type successively occur, the control means, based on the recorded modifications result, modifies a clock for data reproduction.

Claim 31 (Currently Amended): A recording medium holding a packet processing program for use in a packet processor for processing packets of data received via a network to reproduce the data, wherein the packet processor comprises a receiving buffer for storing received packets; a reproducing means for reproducing data of the packets based on a reproduction clock; and a control means for performing control so as to reproduce data without breaks, and

wherein the packet processing program is characterized in that the control means is adapted to control the packets ~~having been~~ stored in the receiving buffer by their number without using temporal information received with the packets, hold ~~[[with]]~~ a reference value for the number of received packets, which is determined beforehand, and cause the reproducing means to start data reproduction when the number of packets exceeds the reference value; the control means is adapted to monitor a state of the receiving buffer and collect, when the packets ~~[[data]]~~ in the buffer are ~~[[is]]~~ used up, packets ~~[[data]]~~ up to a level corresponding to the reference value before causing the reproducing means to restart data reproduction; and the control means is adapted to monitor the number of packets in the receiving buffer at intervals of a predetermined time period and when a result shows increase or decrease in the number of packets with time, the control means is operated to modify, based on the result, a receiving buffer size and the reference value for the number of received packets at which reproduction of data is started.

Claim 32 (Currently Amended): A recording medium holding a packet processing program for use in a packet processor for processing packets of data received via a network to reproduce the data, wherein the packet processor comprises a receiving buffer for storing received packets; a reproducing means for reproducing data of the packets based on a reproduction clock; and a control means for performing control so as to reproduce data without breaks, and

wherein the packet processing program is characterized in that the control means is adapted to control the packets ~~having been~~ stored in the receiving buffer by their number without

using temporal information received with the packets, hold ~~[[with]]~~ a reference value for the number of received packets, which is determined beforehand, and cause the reproducing means to start data reproduction when the number of packets exceeds the reference value; the control means is adapted to monitor a state of the receiving buffer and discard, when the packets ~~[[data]]~~ in the buffer exceed ~~exceeds~~ a predetermined buffer size, a fixed number ~~amount~~ of packets ~~[[data]]~~ from the buffer; and the control means is adapted to monitor the number of packets in the receiving buffer at intervals of a predetermined time period and when a result shows increase or decrease in the number of packets with time, the control means is operated to modify, based on the result, the receiving buffer size and the reference value for the number of received packets at which reproduction of data is started.

Claim 33 (Currently Amended): A recording medium holding a packet processing program for use in a packet processor for processing packets of data received via a network to reproduce the data, wherein the packet processor comprises a receiving buffer for storing received packets; a reproducing means for reproducing data of the packets based on a reproduction clock; and a control means for performing control so as to reproduce data without breaks, and

wherein the packet processing program is characterized in that the control means is adapted to control the packets ~~having been~~ stored in the receiving buffer by their number without using temporal information received with the packets, hold ~~[[with]]~~ a reference value for the number of received packets, which is determined beforehand, and cause the reproducing means to start data reproduction when the number of packets exceeds the reference value; the control means is adapted to monitor a state of the receiving buffer and modify, when the packets ~~[[data]]~~ in the buffer are ~~[[is]]~~ used up, the reference value for the number of received packets at which reproduction of data is started, upon a next reproduction of data; and the control means is adapted to monitor the number of packets in the receiving buffer at intervals of a predetermined time period and when a result shows increase or decrease in the number of packets with time, the control means is operated to modify, based on the result, a receiving buffer size and the reference value for the number of received packets at which reproduction of data is started.

Claim 34 (Currently Amended): A recording medium holding a packet processing program for use in a packet processor for processing packets of data received via a network to reproduce the data, wherein the packet processor comprises a receiving buffer for storing received packets; a reproducing means for reproducing data of the packets based on a reproduction clock; and a control means for performing control so as to reproduce data without breaks, and

wherein the packet processing program is characterized in that the control means is adapted to control the packets ~~having been~~ stored in the receiving buffer by their number without using temporal information received with the packets, hold ~~[[with]]~~ a reference value for the number of received packets, which is determined beforehand, and cause the reproducing means to start data reproduction when the number of packets exceeds the reference value; the control means is adapted to monitor a state of the receiving buffer and modify, when the packets ~~[[data]]~~ in the buffer exceed ~~exceeds~~ a predetermined buffer size, the size of the receiving buffer; and the control means is adapted to monitor the number of packets in the receiving buffer at intervals of a predetermined time period and when a result shows increase or decrease in the number of packets with time, the control means is operated to modify, based on the result, the receiving buffer size and the reference value for the number of received packets at which reproduction of data is started.

Claim 35 (Currently Amended): A recording medium holding a packet processing program for use in a packet processor for processing packets of data received via a network to reproduce the data, wherein the packet processor comprises a receiving buffer for storing received packets; a reproducing means for reproducing data of the packets based on a reproduction clock; and a control means for performing control so as to reproduce data without breaks, and

wherein the packet processing program is characterized in that the control means is adapted to control the packets ~~having been~~ stored in the receiving buffer by their number without using temporal information received with the packets, hold ~~[[with]]~~ a reference value for the number of received packets, which is determined beforehand, and cause the reproducing means to start data reproduction when the number of packets exceeds the reference value; the control means is adapted to monitor a state of the receiving buffer and collect, when the packets ~~[[data]]~~

in the buffer are ~~[[is]]~~ used up, packets ~~[[data]]~~ up to a level corresponding to the reference value before causing the reproducing means to restart data reproduction; and the control means is adapted to monitor the number of packets in the receiving buffer at intervals of a predetermined time period and when a result shows increase or decrease in the number of packets with time, the control means is operated to modify, based on the result, and not based on the temporal information received with the packets, a clock for data reproduction.

Claim 36 (Currently Amended): A recording medium holding a packet processing program for use in a packet processor for processing packets of data received via a network to reproduce the data, wherein the packet processor comprises a receiving buffer for storing received packets; a reproducing means for reproducing data of the packets based on a reproduction clock; and a control means for performing control so as to reproduce data without breaks, and

wherein the packet processing program is characterized in that the control means is adapted to control the packets ~~having been~~ stored in the receiving buffer by their number without using temporal information received with the packets, hold ~~[[with]]~~ a reference value for the number of received packets, which is determined beforehand, and cause the reproducing means to start data reproduction when the number of packets exceeds the reference value; the control means is adapted to monitor a state of the receiving buffer and discard, when the packets ~~[[data]]~~ in the buffer exceed ~~exceeds~~ a predetermined buffer size, a fixed number ~~amount~~ of packets ~~[[data]]~~ from the buffer; and the control means is adapted to monitor the number of packets in the receiving buffer at intervals of a predetermined time period and when a result shows increase or decrease in the number of packets with time, the control means is operated to modify, based on the result, a clock for data reproduction.

Claim 37 (Currently Amended): A recording medium holding a packet processing program for use in a packet processor for processing packets of data received via a network to reproduce the data, wherein the packet processor comprises a receiving buffer for storing received packets; a reproducing means for reproducing data of the packets based on a reproduction clock; and a control means for performing control so as to reproduce data without breaks, and

wherein the packet processing program is characterized in that the control means is adapted to control the packets ~~having been~~ stored in the receiving buffer by their number without using temporal information received with the packets, hold ~~[[with]]~~ a reference value for the number of received packets, which is determined beforehand, and cause the reproducing means to start data reproduction when the number of packets exceeds the reference value; the control means is adapted to monitor a state of the receiving buffer and modify, when the packets ~~[[data]]~~ in the buffer are ~~[[is]]~~ used up, the reference value for the number of received packets at which reproduction of data is started, upon a next reproduction of data; and the control means is adapted to monitor the number of packets in the receiving buffer at intervals of a predetermined time period and when a result shows increase or decrease in the number of packets with time, the control means is operated to modify, based on the result, a clock for data reproduction.

Claim 38 (Currently Amended): A recording medium holding a packet processing program for use in a packet processor for processing packets of data received via a network to reproduce the data, wherein the packet processor comprises a receiving buffer for storing received packets; a reproducing means for reproducing data of the packets based on a reproduction clock; and a control means for performing control so as to reproduce data without breaks, and

wherein the packet processing program is characterized in that the control means is adapted to control the packets ~~having been~~ stored in the receiving buffer by their number without using temporal information received with the packets, hold ~~[[with]]~~ a reference value for the number of received packets, which is determined beforehand, and cause the reproducing means to start data reproduction when the number of packets exceeds the reference value; the control means is adapted to monitor a state of the receiving buffer and modify, when the packets ~~[[data]]~~ in the buffer exceed ~~exceeds~~ a predetermined buffer size, the size of the receiving buffer; and the control means is adapted to monitor the number of packets in the receiving buffer at intervals of a predetermined time period and when a result shows increase or decrease in the number of packets with time, the control means is operated to modify, based on the result, and not based on the temporal information received with the packets, a clock for data reproduction.

Claim 39 (Currently Amended): A recording medium holding a packet processing program for use in a packet processor for processing packets of data received via a network to reproduce the data, wherein the packet processor comprises a receiving buffer for storing received packets; a reproducing means for reproducing data of the packets based on a reproduction clock; and a control means for performing control so as to reproduce data without breaks, and

wherein the packet processing program is characterized in that the control means is adapted to control the packets ~~having been~~ stored in the receiving buffer by their number without using temporal information received with the packets, hold ~~[[with]]~~ a reference value for the number of received packets, which is determined beforehand, and cause the reproducing means to start data reproduction when the number of packets exceeds the reference value; the control means is adapted to monitor a state of the receiving buffer and modify, when the packets ~~[[data]]~~ in the buffer are ~~[[is]]~~ used up, the reference value for the number of received packets at which reproduction of data is started, upon a next reproduction of data; and the control means is adapted to record ~~[[the]]~~ modifications of the reference value for the number of received packets or a receiving buffer size, continuously from a start of a communication, and if recorded modifications of one type successively occur, the control means is operated to modify, based on the recorded modifications ~~result~~, the receiving buffer size and the reference value for the number of received packets at which reproduction of data is started.

Claim 40 (Currently Amended): A recording medium holding a packet processing program for use in a packet processor for processing packets of data received via a network to reproduce the data, wherein the packet processor comprises a receiving buffer for storing received packets; a reproducing means for reproducing data of the packets based on a reproduction clock; and a control means for performing control so as to reproduce data without breaks, and

wherein the packet processing program is characterized in that the control means is adapted to control the packets ~~having been~~ stored in the receiving buffer by their number without using temporal information received with the packets, hold ~~[[with]]~~ a reference value for the number of received packets, which is determined beforehand, and cause the reproducing means to start data reproduction when the number of packets exceeds the reference value; the control

means is adapted to monitor a state of the receiving buffer and modify, when the packets [[data]] in the buffer exceed ~~exceeds~~ a predetermined buffer size, the size of the receiving buffer; and the control means is adapted to record [[the]] modifications of the reference value for the number of received packets or the receiving buffer size, continuously from a start of a communication, and if recorded modifications of one type successively occur, the control means is operated to modify, based on the recorded modifications ~~result~~, the receiving buffer size and the reference value for the number of received packets at which reproduction of data is started.

Claim 41 (Currently Amended): A recording medium holding a packet processing program for use in a packet processor for processing packets of data received via a network to reproduce the data, wherein the packet processor comprises a receiving buffer for storing received packets; a reproducing means for reproducing data of the packets based on a reproduction clock; and a control means for performing control so as to reproduce data without breaks, and

wherein the packet processing program is characterized in that the control means is adapted to control the packets ~~having been~~ stored in the receiving buffer by their number without using temporal information received with the packets, hold [[with]] a reference value for the number of received packets, which is determined beforehand, and cause the reproducing means to start data reproduction when the number of packets exceeds the reference value; the control means is adapted to monitor a state of the receiving buffer and modify, when the packets [[data]] in the buffer are [[is]] used up, the reference value for the number of received packets at which reproduction of data is started, upon a next reproduction of data; and the control means is adapted to record [[the]] modifications of the reference value for the number of received packets or a receiving buffer size, continuously from a start of a communication, and if recorded modifications of one type successively occur, the control means is adapted to modify, based on the recorded modifications ~~result~~, a clock for data reproduction.

Claim 42 (Currently Amended): A recording medium holding a packet processing program for use in a packet processor for processing packets of data received via a network to reproduce the data, wherein the packet processor comprises a receiving buffer for storing received packets; a reproducing means for reproducing data of the packets based on a

reproduction clock; and a control means for performing control so as to reproduce data without breaks, and

wherein the packet processing program is characterized in that the control means is adapted to control the packets ~~having been~~ stored in the receiving buffer by their number without using temporal information received with the packets, hold ~~[[with]]~~ a reference value for the number of received packets, which is determined beforehand, and cause the reproducing means to start data reproduction when the number of packets exceeds the reference value; the control means is adapted to monitor a state of the receiving buffer and modify, when the packets ~~[[data]]~~ in the buffer ~~exceed~~ ~~exceeds~~ a predetermined buffer size, the size of the receiving buffer; and the control means is adapted to record ~~[[the]]~~ modifications of the reference value for the number of received packets or the receiving buffer size, continuously from a start of a communication, and if recorded modifications of one type successively occur, the control means is adapted to modify, based on the recorded modifications ~~result~~, a clock for data reproduction.

Claim 43 (Currently Amended): A packet processor for processing packets of data received via a network, comprising:

a receiving buffer for storing received packets; and

a controller that controls packets stored in the receiving buffer by their number without using temporal information received with the packets, holds a reference value for the number of received packets, and initiates data reproduction when the number of packets in the receiving buffer exceeds the reference value ~~number~~; monitors a state of the receiving buffer and collects, when the packets ~~[[data]]~~ in the receiving buffer is used up, packets ~~[[data]]~~ up to a level corresponding to the reference value before initiating a restart of data reproduction; and monitors the number of packets in the receiving buffer at specified time intervals, and when a result of the packet number monitoring shows non-jitter-induced increases or decreases over time in the number of packets in the receiving buffer, modifies both a receiving buffer size and the reference value for the number of received packets at which reproduction of data is initiated.

Claim 44 (Currently Amended): A packet processing program for processing packets of data received via a network, the packet processing program being tangibly embodied on a recording medium and which, when executed, performs a method comprising:

storing received packets;

controlling packets stored in the receiving buffer by their number without using temporal information received with the packets, holding a reference value for the number of received packets, and initiating data reproduction when the number of packets in the receiving buffer exceeds the reference value number;

monitoring a state of the receiving buffer and collecting, when the packets [[data]] in the receiving buffer are [[is]] used up, packets [[data]] up to a level corresponding to the reference value before initiating a restart of data reproduction; and

monitoring the number of packets in the receiving buffer at specified time intervals, and when a result of the packet number monitoring shows non-jitter-induced increases or decreases over time in the number of packets in the receiving buffer, modifying both a receiving buffer size and the reference value for the number of received packets at which reproduction of data is initiated.